

# 17"

## Professional Video TFT LCD Monitor



### Features:

- Special Video Processor
- VESA Standard Bracket
- Automatic Color Control and Color Killer
- PIP Control Function (PC/Video)
- 3D Comb Filter Technology
- 3D De-Interlace Technology
- Friendly OSD Menu
- Sharpness Enhancement
- Black Level Extension
- Monitor Identification Setting Function
- Short Response Time Between Source Switching
- With M-Star IC
- 10 Bit Display Color Processing
- Plastic Panel Frame, Metal Case

Model	CH-L171AV-1MDEL	CH-L172AV-3HMDEL
Operating System	NTSC / PAL Auto Switch	
LCD Panel	17" TFT	
Viewable area (H/Vmm)	338 x 270	
Profile Ratio	5:4	
Max. Resolution (H/V)	1280 x 1024	
Display Colors	16.7M	
Brightness (nit)	250 (LED BL)	
Contrast Ratio	1000:1	
Response Time (TR/Tf)	3.5 / 1.5 ms	
Viewing Angle (U/D/L/R)	80/80/80/80	
Video Input/Output	2x / 2x Composite (BNC), 1x S-Video Input, 1x VGA Input (D-Sub 15 pin) / 1x Earphone	2x BNC In/Out, 1x S-Video Input, 1x VGA Input, 1x HDMI Input
Audio Input/Output	2x / 2x (RCA)	2x Audio R/L, 1x PC Audio
Speaker	Audio Speaker x 2 (2W + 2W)	Audio Speaker x 2 (2W + 2W)
Input/Output Impedance	75Ω Auto Termination	
3D Comb Filter	YES	
3D De-Interlace Function	YES	
Picture-in-Picture (PIP)	YES (PC/Video)	
OSD Function	YES	
Panel Frame	Plastic	Aluminum
Environment	Operating: 0 °C ~50 °C (32°F~122°F)/ Humidity: 10% ~ 85% Storage: -21°C~ 60°C (14°F~140°F)/ Humidity: 10% ~ 85%	Operating: 0 °C ~50 °C (32°F~122°F)/ Humidity: 10% ~ 85% Storage: -10°C~ 60°C (14°F~140°F)/ Humidity: 10% ~ 85%
Power Consumption	Approx. 30W	
Power Supply	AC 90~264V AC 60/50Hz, Global Switching Adapter 12V/3A	AC 100~240V 50/60Hz, Adapter DC 12V/5A
Net Dimensions (W*H*D)	15.39 x 12.79 x 2.7	15.39 x 12.79 x 2.7
Net Weight	4.5kg (9.92lbs)	

\*Specifications are subject to change without notice